

OAP-Styleguide

(Version 1.4)

Author: Annett Wiegand <Annett.Wiegand@EasternGraphics.com>

Until there is a tool to develop OAP, these tables have to be written manually. Doing this one can loose track very easily. To avoid confusion here is a little styleguide.

Each key will be prefixed with unique combination of letters indicating the table they are referring to.

Following this styleguide simplifys orientation in one's own tables. It also improves and expedites support by EasternGraphics staff.

Basically IDs can be chosen freely, as long as they consist of alphanumeric characters and do not start with a digit. For the sake of readability camel case (a mix of upper case **and** lower case letters) should be preferred.

Key	Prefix	Example
A		
ActionChoice	ACH_	ACH_addableChildren
ActionList	ACL_	ACL_addableChildren
Action	AC_	AC_...
CreateObj-Action	AC_CO_	AC_CO_Table
DimChange-Action	AC_DC_	AC_DC_Width
Delete-Action	AC_DL_	AC_DL_Table
PropertyChange-Action	AC_PC_	AC_PC_colorGreen
PropEdit-Action	AC_PE_	AC_PE_Colors
ShowMedia-Action	AC_SM_	AC_SM_Video
SelectObj-Action	AC_SO_	AC_SO_Father
MethodCall-Action	AC_call_	AC_call_setPropValue_Color_green The action's ID should correspond to the MethodCall's ID, with MC being replaced by AC_call.
ActionChoice-Action	AC_choice_	AC_choice_colors
C		
CreateObject	CO_	CO_Table12345
D		
DimChange	DC_	DC_Width
E		
ExtMedia	XM_	XM_Video
I		
Interactor	IA_	IA_addTableR
Image	IMG_	IMG_AttachTableTop
M		
MethodCalls	MC_	MC_doSomething
Message	MSG_	MSG_info
N		
NumTriple	NT_	NT_leftArmRest
O		
OAP-Typ	OAP_	OAP_Table
Object	OB_	OB_self

Key	Prefix	Example
P		
PropChange	PC_	PC_addArmRest
PropEdit (deprecated)	PE_	PE_mainPropsForTP
PropEdit2	PE_	PE_mainPropsForTP
PropEditProp	PE_PR_	PE_PR_Color
PropEditClass	PE_CL_	PE_CL_Dimension
T		
Text	TXT_	TXT_AttachTableTop
Text for title	TXT_Title_	TXT_Title_Properties